

```

Stopwatch : process (Play, Rst, Clock)
  variable Count: integer := 0;
begin
  if Rst = '1' then
    Count := 0;
    Digit1 <= 0; -- Controls the first digit of the seven segment
    Digit2 <= 0; -- Controls the second digit of the seven segment
    Digit3 <= 0; -- Controls the third digit of the seven segment
    Digit4 <= 0; -- Controls the fourth digit of the seven segment
    Fail <= '0'; -- Fail is our fail signal, which once triggered, will go to the stage "111011"
  elsif Play = '0' then -- If Play is off, then count will be held to the value as it was
    Count := Count;
  elsif Play = '1' and rst = '0' then
    if (rising_edge(Clock)) then
      Count := Count + 1;
      if Count = 100000 then -- Count will only increment Digit0 every thousandth of a
second
        Digit1 <= Digit1 + 1;
        Count := 0;
        if Digit1 = 9 then
          Digit2 <= Digit2 + 1;
          Digit1 <= 0;
          if Digit2 = 9 then
            Digit3 <= Digit3 + 1;
            Digit2 <= 0;
            if Digit3 = 9 then
              Digit4 <= Digit4 + 1;
              Digit3 <= 0;
              if Digit4 = 9 then -- Once the last digit rolls over
                digit4 <= 0;
                Fail <= '1';
              end if;
            end if;
          end if;
        end if;
      end if;
    end if;
  end if;
end process;

```

Seven_Seg_Display : process (Clock, Digit1, Digit2, Digit3, Digit4) -- Controls the 7 Segment Display on the Basys Board

```

  variable counting : integer := 0;
```

```

begin
  if (rising_edge(Clock)) then
    Counting := counting +1;
    If Counting = 1 then
      Anode <= "1110"; --Utilize Right-Most Digit of 7-Segment Only
      If Digit1 = 0 then --0
        Cathode <= "00000011";
      elsif Digit1 = 1 then --1
        Cathode <= "10011111";
      elsif Digit1 = 2 then --2
        Cathode <= "00100101";
      elsif Digit1 = 3 then --3
        Cathode <= "00001101";
      elsif Digit1 = 4 then --4
        Cathode <= "10011001";
      elsif Digit1 = 5 then --5
        Cathode <= "01001001";
      elsif Digit1 = 6 then --6
        Cathode <= "01000001";
      elsif Digit1 = 7 then --7
        Cathode <= "00011111";
      elsif Digit1 = 8 then --8
        Cathode <= "00000001";
      elsif Digit1 = 9 then--9
        Cathode <= "00011001";
    end if;
  elsif Counting = 400000 then -- Refreshes the Second Right-Most Segment
    Anode <= "1101";
    If Digit2 = 0 then --0
      Cathode <= "00000011";
    elsif Digit2 = 1 then --1
      Cathode <= "10011111";
    elsif Digit2 = 2 then --2
      Cathode <= "00100101";
    elsif Digit2 = 3 then --3
      Cathode <= "00001101";
    elsif Digit2 = 4 then --4
      Cathode <= "10011001";
    elsif Digit2 = 5 then --5
      Cathode <= "01001001";
    elsif Digit2 = 6 then --6
      Cathode <= "01000001";
    elsif Digit2 = 7 then --7

```

```

        Cathode <= "00011111";
elsif Digit2 = 8 then --8
        Cathode <= "00000001";
elsif Digit2 = 9 then--9
        Cathode <= "00011001";
end if;
elsif Counting = 800000 then -- Refreshes the Second Left-Most Segment
    Anode <= "1011";
    If Digit3 = 0 then --0
        Cathode <= "00000011";
    elsif Digit3 = 1 then --1
        Cathode <= "10011111";
    elsif Digit3 = 2 then --2
        Cathode <= "00100101";
    elsif Digit3 = 3 then --3
        Cathode <= "00001101";
    elsif Digit3 = 4 then --4
        Cathode <= "10011001";
    elsif Digit3 = 5 then --5
        Cathode <= "01001001";
    elsif Digit3 = 6 then --6
        Cathode <= "01000001";
    elsif Digit3 = 7 then --7
        Cathode <= "00011111";
    elsif Digit3 = 8 then --8
        Cathode <= "00000001";
    elsif Digit3 = 9 then--9
        Cathode <= "00011001";
end if;
elsif Counting = 1200000 then --Refreshes the Left-Most digit of the 7 Segment
    Anode <= "0111";
    If Digit4 = 0 then --0
        Cathode <= "00000010";
    elsif Digit4 = 1 then --1
        Cathode <= "10011110";
    elsif Digit4 = 2 then --2
        Cathode <= "00100100";
    elsif Digit4 = 3 then --3
        Cathode <= "00001100";
    elsif Digit4 = 4 then --4
        Cathode <= "10011000";
    elsif Digit4 = 5 then --5
        Cathode <= "01001000";

```

```
elsif Digit4 = 6 then --6
    Cathode <= "01000000";
elsif Digit4 = 7 then --7
    Cathode <= "00011110";
elsif Digit4 = 8 then --8
    Cathode <= "00000000";
elsif Digit4 = 9 then--9
    Cathode <= "00011000";
end if;
elsif Counting = 1600000 then -- Resets Counting to 0, which repeats this process
    Counting := 0;
end if;
end if;
end process;
```